





# Polypropylene and Foil Capacitors



(All dimensions in inches)



# 1206EFR

## Epoxy Case (Radial Leads)

Lead Specs.  
Tinned Copperweld  
B through E cases: 22 AWG  
F through Q cases: 20 AWG

## DIMENSIONS and RATINGS

Cap. μF	63/40 VDC/VAC	160/100 VDC/VAC	250/160 VDC/VAC	400/220 VDC/VAC	630/250 VDC/VAC	CASE SIZE	L <u>mm</u> in.	T <u>mm</u> in.	H <u>mm</u> in.	S <u>mm</u> in.
.001	B	B	B	B	C	B	10.5	4	9	7.5
.0012	B	B	B	B	C	C	.413	.157	.354	.295
.0015	B	B	B	B	C	C	13	4	9	10
.0022	B	B	B	C	D	D	.512	.157	.354	.394
.0027	B	B	B	C	D	D	13	5	11	10
.0039	B	B	B	C	E	E	.512	.197	.433	.394
.0047	B	B	C	C	F	F	13	6	12	10
.0056	B	B	C	C	F	F	.512	.236	.472	.394
.0068	B	B	C	D	G	G	18	5	11	15
.0082	B	C	C	E	G	G	.709	.197	.433	.591
.01	B	C	C	E	H	H	18	6	12	15
.012	C	C	C	F	H	H	.709	.236	.472	.591
.015	C	C	D	G	J/L	J/L	18	7.5	13.5	15
.018	C	C	D	H	J/L	J/L	.709	.295	.531	.591
.022	C	D	E	H	K/M	K/M	26.5	6	15	20
.027	D	D	E	H	N	N	1.04	.236	.591	.787
.033	D	E	G	J/L	N	N	26.5	7	16	20
.039	E	E	G	K/M	O	O	1.04	.276	.630	.787
.047	E	F	H	K/M	O	O	26.5	6	15	22.5
.056	E	G	H	N	P	P	1.04	.236	.591	.886
.068	G	G	J/L	N	P	P	26.5	7	16	22.5
.082	G	H	K/M	O	P	P	1.04	.276	.630	.886
.1	H	H	K/M	P	Q	Q	26.5	8.5	16.3	22.5
.12	H	J/L	N	P	Q	Q	1.04	.335	.642	.886
.15	J/L	K/M	O	P			26.5	10	19	22.5
.18	K/M	N	O	Q			1.04	.394	.748	.886
.22	N	N	P	Q			32	11	20	27.5
.27	N	O	P				1.26	.433	.787	1.08
.33	O	O	P				32	13	22	27.5
.39	O	P	Q				1.26	.512	.866	1.08
.47	P	P								
.56	P	Q								
.68	P									
.82	Q									

### ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park \* 41 Interstate Lane \* WATERBURY, CONNECTICUT 06705

Phone (203) 755-5629

FAX (203) 755-0659

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.