





Polystyrene and Foil Capacitors



(All dimensions in inches)

1906EC

**Epoxy Case
(Axial Leads)**

Lead Specs.

Tinned Copperweld

Under .250D = 24 AWG

.250 - .440D = 22 AWG

Above .440D = 20 AWG

DIMENSIONS and RATINGS

Cap. μF	1906EC 50 VDC		1906EC 100 VDC		1906EC 200 VDC		1906EC 400 VDC		1906EC 600 VDC			
	D	L	D	L	D	L	D	L	D	L		
.001	1	A	1	A	2	A	1	B	2	C		
.0012	1	A	1	A	2	A	2	B	2	C		
.0015	1	A	1	A	2	A	2	B	3	C		
.0022	2	A	2	A	2	B	3	B	4	C		
.0027	2	A	2	A	2	B	3	B	4	C		
.0039	1	B	2	B	2	B	3	C	4	D		
.0047	1	B	2	B	3	B	3	C	5	D		
.0056	2	B	2	B	3	C	4	C	5	D		
.0068	2	B	2	B	3	C	4	C	5	E		
.0082	2	B	3	B	3	C	4	D	6	E		
.01	2	B	3	B	4	C	4	D	6	F		
.012	3	B	3	C	4	C	5	D	6	F		
.015	3	C	3	C	4	D	5	D	6	F		
.018	3	C	4	C	4	D	5	E	7	F		
.022	4	C	4	D	5	D	6	E	7	F		
.027	4	C	4	D	5	D	6	E				
.033	4	C	4	D	5	E	7	E				
.039	4	D	5	D	6	E	7	F				
.047	5	D	5	D	6	E	7	F				
.056	5	D	5	D	7	E						
.068	5	D	5	E	6	F						
.082	5	E	6	E	7	F						
.1	6	E	6	E								
.12	6	E	7	E								
.15	7	E	7	F								
.18	7	F	7	F								
.22	7	F										

DIAMETER

1 = .187 5 = .375
 2 = .225 6 = .437
 3 = .250 7 = .500
 4 = .312

SIZE CODE

LENGTH

A = .375 D = .750
 B = .500 E = .875
 C = .625 F = 1.190

ELECTRONIC FILM CAPACITORS, INC.

Reidville Industrial Park * 41 Interstate Lane * WATERBURY, CONNECTICUT 06705
 Phone (203) 755-5629 FAX (203) 755-0659

EFC will manufacture to any non-standard value and size. Please consult factory for special requirements.